

Minivac 2

Light Weight Vacuum Pump



JAVAC's Minivac 2 fulfills the market's need for a reliable, compact 2 stage vacuum pump. Weighing in at only 4.5kg, it is ideally suited for light duty or emergency jobs.



TECHNICAL SPECIFICATIONS

Frequency
50Hz

Free Air Displacement
28 litres per minute

Ultimate Vacuum
38 microns (0.038mbar)

Motor Power
200 watts

Oil Capacity
140 ml

Inlet Fittings
1/4 Flare & 1/2" ACME

Dimensions
260mm x 90mm x 165mm

Net Weight
4.5 kg

Warranty
12 months

Not suitable for use with ammonia

The Minivac 2 is a two stage 28 litre per minute vacuum pump, capable of an ultimate vacuum of 38 microns (0.038mbar). Suitable for most refrigerants, this light weight unit is extremely versatile when endeavouring to reach inconvenient work areas such as remote plant rooms or roof tops.

Features at a Glance

- Integrated design of motor and pump means a compact and simple to use unit
- High starting torque enables easy start in low temperature conditions
- Anti-oil Return
 - The air passage is designed to prevent oil from returning to contaminate the chamber and pipeline after the pump has stopped
- Integrated Demister
 - A built in device eliminates oil mist; and an oil gas separator at the air exhaust outlet reduces oil contamination in the air exhaust